Page 1 of 6 First issue: 2016/06/30

Revised:

SDS # CPS-F-0053M / Cellufine MAX AminoButyl

Chromatography Media

# Safety Data Sheet Cellufine™ MAX AminoButyl

### 1. Product & Company Identification

Product Name : Cellufine MAX AminoButyl
General Use : Liquid Chromatography Media

Product Description : Beads slurry of cross-linked cellulose containing both amino and butyl

group in 20% of EtOH/H2O

SDS Number : CPS-F-0053M

Manufacturer

Company Name : JNC CORPORATION

Address : Shin-Otemachi BLDG., 2-1, Otemachi 2-chome, Chiyoda-ku, Tokyo

100-8105, Japan

Tel : +81-3-3243-6150 Fax : +81-3-3243-6219 Emergency telephone number : +81-3-3243-6150

### 2. Hazards identification

Hazard classification: Flammable Liquids - Category 3

GHS label elements
Signal word: Warning

Hazard statements: Flammable liquid and vapor

Pictograms:



#### Precautionary statements:

Keep away from heat/sparks/open flames/hot surfaces. – No smoking.

Keep container tightly closed. Use explosion-proof equipment.

Use only non-sparking tools.

Take precautionary measures against static discharge.

Wear protective gloves/eye protection/face protection.

If on skin (or hair): Take off immediately all contaminated clothing.

Rinse skin with water/shower.

In case of fire: Use carbon dioxide, dry chemical powder, alcohol resistant foam, or water to extinguish.

Dispose of contents/container in accordance with local/regional/national/international regulations.

Unclassified hazards:

May be harmful if inhaled and ingested.

May cause eye and skin irritation.

Page 2 of 6 First issue: 2016/06/30

Revised:

SDS # CPS-F-0053M / Cellufine MAX AminoButyl

Percentage of ingredients with unknown toxicity: Not applicable

### 3. Composition/Information on ingredients

Classification of the Substance or Mixture: Mixture

Component	Wt %	CAS No.	Chemical Formula
Cellufine MAX Aminobutyl	10	NA	HO
EtOH	8 – 18	64-17-5	CH <sub>3</sub> CH <sub>2</sub> OH
Water	72 – 82	7732-18-5	H <sub>2</sub> O

The specific percentages of composition have been withheld as trade secrets.

#### 4 First aid measures

4. First aid measures	
General advice	: Wash off immediately with soap and plenty of water. In the case of inhaling dust and/or fumes, use self-contained breathing apparatus and dust impervious protective suit.  Use personal protective equipment.
Inhalation	<ul> <li>: Move victim to fresh air. If breathing is difficult, give oxygen. If irritation persists, consult physician.</li> </ul>
Eye	: Remove any contact lenses at once. Fresh eyes well with flooding amounts of running water for at least 15 minutes. Assure adequate flushing by separating the eyelids with sterile fingers. If irritation persists, consult a physician.
Skin	: Remove contaminated clothes and shoes, rinse skin with plenty of water or shower. Use soap to help assure removal. If irritation persists, consult a physician.
Ingestion	: Rinse mouth and give plenty of water to dilute the substance. Never give anything by mouth to an unconscious person. Consult a physician.
Protection to first-aides	: Rescuers wear suitable protective equipment such as rubber gloves and tight-fitting safety goggles.
Note to physician	: Treatment may vary with condition of victim and specifics of incident.

Page 3 of 6 First issue: 2016/06/30

Revised:

SDS # CPS-F-0053M / Cellufine MAX AminoButyl

5. Fire-fighting measures

Flammable properties : Flammable

Extinguishing media : Carbon dioxide, dry chemical powder, alcohol resistant form, water

Specific hazards : Carbon monoxide and nitrogen oxides may be formed

Fire-fighting instructions : Wear full fire-fighting turnout gear (full banker gear) and respiratory

protection (self-contained breathing apparatus).

6. Accidental release measures

Personal precautions : Remove ignition sources and ventilate area. In case of insufficient

ventilation, wear suitable respiratory

Environmental precautions : Prevent spills from entering sewers, watercourses or low area.

Methods for clean up : Do not touch spilled material without suitable protection (See section 8).

Take up spilled material with ashes or other absorbents. After material is completely picked up, wash the spill site with soap and water and ventilate the area. Put all waste in a plastic bag for disposal and seal it tightly.

Remove, clean, or dispose of contaminated clothing.

7. Handling and storage

Handling : Avoid contact with eyes, skin, and clothing. Avoid prolonged or repeated

exposure. Handle material with suitable protection.

Storage : After opened bottle store away from sunlight in a cool (2-8 °C {35.6-46.4

°F)) well –ventilated dry place.

Incompatible products : Oxidizers, peroxides, acids, alkalis, anhydrides

8. Exposure controls/personal protection

Engineering measures : Use exhaust ventilation to keep airborne concentrations below exposure

limits. Use only with adequate ventilation.

Ventilation : Local exhaust ; Necessary, Mechanical (General) ; Recommended

Control parameter

OSHA Final limits : None established (Cellufine MAX AminoButyl),

TWA= 1000 ppm, 1900 mg/m<sup>3</sup> (EtOH)

ACGIH TLV(s) : None established (Cellufine MAX AminoButyl),

TWA= 1000 ppm, 1880 mg/m<sup>3</sup> (EtOH)

Personal protection

Respiratory protection : None established (Cellufine MAX AminoButyl)

Hand protection : Chemical resistant gloves
Eye protection : Safety glasses (goggles)
Skin protection : Protective clothing

Page 4 of 6 First issue: 2016/06/30

Revised:

SDS # CPS-F-0053M / Cellufine MAX AminoButyl

### 9. Physical and chemical properties

Appearance : White-slightly grayish slurry

**ODOR** : Not available Odor threshold : Not available рН : Not available Boiling point : Not available Melting point : Not available : 35 - 38°C Flash point Evaporation rate : Not available Flammability (solid, gas) : Not applicable Decomposition temperature : Not available **Explosive limits** : Not available Vapor pressure : Not available Vapor density : Not available Specific gravity : Not available Solubility in; Water : Insoluble log Po/w : Not available : Not available Autoignition temperature : Not available Viscosity

#### 10. Stability and reactivity

Reactivity : No data available
Chemical stability : No data available
Condition to avoid : Sunlight, heat

Incompatibility (material to avoi : Oxidizers, acids, alkalis

d)

Hazardous decomposition: Carbon monoxide and nitrogen oxides may be formed

products

Hazardous polymerization : Will not occur.

Page 5 of 6 First issue: 2016/06/30

Revised:

SDS # CPS-F-0053M / Cellufine MAX AminoButyl

11. Toxicological information				
	Cellufine MAX AminoButyl	EtOH		
Acute toxicity data	: Not available	: TDLo (oral, infant): 11712 µL/kg (JOUOD4 9, 53, 1987) : TDLo (oral, man): 700mg/kg (NTOTDY 8, 77, 1986) : LD50 (oral, rat): 9,000mg/kg (VCVGK* -,93, 1984) : LC50 (ihl, rat): 20,000ppm/10H (NPIRI* 1, 44, 1974)		
Irritation data	: Not available	: Skin; rabbit; 20mg/24H; Moderate (85JCAE -, 189, 1986) : Eye; rabbit; 500mg/24H; Mild (85JCAE -, 189, 1986)		
Mutation data	: Not available	<ul> <li>: DNA damage; S. cerevisiae; 850mmol/L (MUREAV326, 165, 1995)</li> <li>: Mutation in microorganisms; S. typhimurium; 11pph (ENVRAL 52, 225, 1990)</li> <li>: Cytogenetic analysis; human; lymphocyte; 2.5pph/24H (MUREAV 537,117, 2003)</li> </ul>		
Reproductive effects	: Not available	: TDLo (oral, woman): 250mg/kg (37 W preg); Effects on embryo or Fetus – other effects to embryo (AJOGAH 145, 251, 1983) TDLo (oral, rat): 22.5mg/kg (11-20 D preg); Specific Developmental Abnormalities – Central Nervous Systems (NETEEC 24, 719, 2002)		
Tumorigenic data	: Not available	: TDLo (oral, mouse): 320mg/kg/50W-I (CALEDQ 13, 345, 1981)		

### 12. Ecological information

Cellufine MAX EtOH

AminoButyl

Biodegradability : Not available : Biodegradable
Bioaccumulation potential : Not available : Not available
Aquatic toxicity : Not available : Not available
Other information : Not available : WGK; 1

## 13. Disposal consideration

Burn in a chemical incinerator equipped with an afterburner and scrubber in accordance with all applicable regulations. Any disposal practice must be in compliance with country, local or state and federal laws and regulations (contact country, local or state environmental agency for specific rules).

Page 6 of 6 First issue: 2016/06/30

Revised:

SDS # CPS-F-0053M / Cellufine MAX AminoButyl

14. Transport information

UN number : 1170 (Not applicable : An aqueous solution containing not more than 24% alcohol

by volume is not subject to the requirements)

Class : 3 Packing group : II

RID/ADR : Not Classified. An aqueous solution containing not more than 24% alcohol by

volume is not subject to the requirements of RID/ADR. (SP No. 144)

IMDG : Not Classified. An aqueous solution containing not more than 24% alcohol by

volume is not subject to the provisions of IMDG Code. (SP No. 144)

ICAO/IATA : Not Classified. An aqueous solution containing not more than 24% alcohol by

volume is not subject to Dangerous Goods Regulations. (SP No. A58(144))

US DOT : Not Classified. An agueous solution containing no less than 50 percent water,

24 percent or less alcohol by volume and no other hazardous materials is

exempted from hazardous material under 49CFR173.150(e)(2).

15. Regulatory information

Cellufine MAX EtOH

AminoButyl

US Regulations : Not listed : CAA/111 Volat. Org. Comp, NIOSH Recommend.

Subst., IARC Subst. Overall Eval., NTP Test. Prog., DOT Haz.

Mat., Mass. Subst. List, New Jers. RTK Haz. Subst. List,

Canada WHMIS IDL 0.1% conc.

EU regulations : Not listed : SYMBOL: F

R-phrases: 11 S-phrases: 7-16

Keep container tightly closed.

Keep away from sources of –No smoking.

EC index No: 603-002-00-5

#### 16. Other information

This information is furnished without warranty, express or implied, except that it is accurate to the best knowledge of JNC Corporation. It relates to only to the specific product designated herein, and does not relate to use in combination with any other material or in any process. JNC Corporation assumes no legal responsibility for use of or reliance upon this information.